



MULTI-PURPOSE SYNTHETIC GREASE

SUPER LUBE® WITH SYNCOLON® (PTFE)

Super Lube® Grease is a patented synthetic heavy-duty, multi-purpose lubricant with Syncolon® (PTFE). Synthetic base fluids and the addition of Syncolon® (PTFE) micro powders combine to form a premium lubricant that provides longer life protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced and productivity is increased.

Super Lube® Grease is a NSF registered Food Grade lubricant, rated H1 for incidental food contact. Meets former USDA (H1) guidelines.

Super Lube® Grease offers good mechanical stability, does not evaporate or form gummy deposits. It will not melt or separate.

There is no Silicone in Super Lube® Multi-Purpose Grease with Syncolon® (PTFE). It is safe for use in paint spraying and finishing operations.



BENEFITS

- ✓ Dielectric
- ✓ Food grade and clean
- ✓ Will not drip, run or evaporate
- ✓ Impervious to salt water, safe in potable water
- ✓ Long lasting
- ✓ Prevents rust and corrosion while reducing friction
- ✓ Wide temperature range
- ✓ Compatible with most other greases
- ✓ Excellent water resistance and rust inhibiting properties
- ✓ Outlasts conventional greases 3 to 4 times
- ✓ NSF Registered (H1), # 096790
- ✓ Environmentally friendly
- ✓ Biodegradable
- ✓ NLGI GC-LB Approved for Grade 2 only
- ✓ Kosher Certified

Part Numbers:	
47-41150/00	14 oz. Cartridge
47-41030/00	30 lb. Pail
47-41120/00	120 lb. Keg



*For Total Lube Solutions,
GO WITH THE FLO!*

FLO Components Ltd., 50 Admiral Blvd., Mississauga, ON, L5T 2W1
1.800.668.5458 • sales@flocomponents.com • www.flocomponents.com



TECHNICAL DATA SHEET

SUPER-LUBE® MULTIPURPOSE SYNTHETIC GREASE WITH SYNCOLON® (PTFE)

PROPERTIES:

Test	Test Method	Rating
NLGI Grade:	ASTM D217	2, 1, 0, 00, 000
NLGI Classification:	ASTM D4950	GC-LB* (Only for NLGI 2)
Color:		Translucent White
Temperature Range:		-45°F to 450°F (-43°C to 232°C)
Viscosity (Base Oil)		
cSt @ 100°C:	ASTM D445	8
SUS @ 40°C:	ASTM D445	350
Specific Gravity:	ASTM D1298	.89 @ 60°F
Water, PPM:	ASTM D1744	35 ppm
Tan:	ASTM D974	0.04 maximum

DIRECTIONS:

- Clean and dry area/equipment to be treated.
- When using on bearings, wipe grease fittings clean before pumping grease to avoid contamination. Do not over-grease, as excessive heating may result. Fill bearing 1/3 to 1/2 full normally and monitor to establish a regular maintenance schedule. Periodically clean and repack bearings with fresh grease.
- For best results, we recommend purging other greases before using our product.
- Re-apply as necessary.
- Not for use in a pure oxygen environment.

SHELF LIFE / WARRANTY:

Super Lube® products have a five (5) year recommended shelf life when stored in the original container and in reasonable ambient conditions. The warranty period is twenty-four (24) months from the date of purchase.



For Total Lube Solutions,
GO WITH THE FLO!

FLO Components Ltd., 50 Admiral Blvd., Mississauga, ON, L5T 2W1
1.800.668.5458 • sales@flocomponents.com • www.flocomponents.com